

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2019/0388609 A1 Lanigan et al.

Dec. 26, 2019 (43) **Pub. Date:**

(54) APPARATUS, SYSTEM AND METHOD FOR FLUID DELIVERY

(71) Applicant: **DEKA Products Limited Partnership**, Manchester, NH (US)

Inventors: Richard J. Lanigan, Concord, NH

(US); Bright C.K. Foo, Hollis, NH (US); Dean Kamen, Bedford, NH (US)

(21) Appl. No.: 16/259,615

(22) Filed: Jan. 28, 2019

Related U.S. Application Data

- (63)Continuation of application No. 12/649,681, filed on Dec. 30, 2009, now Pat. No. 10,188,787, which is a continuation-in-part of application No. 12/347,985, filed on Dec. 31, 2008, now Pat. No. 8,491,570, said application No. 12/649,681 is a continuation-in-part of application No. 12/347,982, filed on Dec. 31, 2008, now Pat. No. 9,526,830, said application No. 12/649, 681 is a continuation-in-part of application No. 12/347,984, filed on Dec. 31, 2008, now Pat. No. 8,414,563.
- (60) Provisional application No. 61/142,042, filed on Dec. 31, 2008, provisional application No. 61/225,794, filed on Jul. 15, 2009, provisional application No. 61/018,054, filed on Dec. 31, 2007, provisional application No. 61/018,042, filed on Dec. 31, 2007, provisional application No. 61/017,989, filed on Dec. 31, 2007, provisional application No. 61/018,002, filed on Dec. 31, 2007, provisional application No. (Continued)

Publication Classification

(51)	Int. Cl.	
` ′	A61M 5/14	(2006.01)
	A61J 1/20	(2006.01)
	A61M 5/142	(2006.01)
	A61M 5/168	(2006.01)
	G01F 11/08	(2006.01)
	G05D 7/06	(2006.01)

H01Q 1/27 (2006.01)H01Q 9/26 (2006.01)

U.S. Cl. CPC A61M 5/1413 (2013.01); A61M 2209/086 (2013.01); A61M 5/142 (2013.01); A61M 5/14244 (2013.01); A61M 5/14248 (2013.01); A61M 5/16809 (2013.01); G01F 11/086 (2013.01); G05D 7/0647 (2013.01); G05D 7/0676 (2013.01); H01Q 1/273 (2013.01); H01Q 9/265 (2013.01); A61M 5/16886 (2013.01); A61M 2005/14268 (2013.01); A61M 2205/0266 (2013.01); A61M 2205/18 (2013.01); A61M 2205/3331 (2013.01); A61M 2205/3375 (2013.01); A61M 2205/3393 (2013.01); A61M 2205/3515 (2013.01); A61M 2205/3546 (2013.01); A61M 2205/3569

> 2205/50 (2013.01); A61M 2205/59 (2013.01); A61M 2205/6018 (2013.01); A61M 2205/70 (2013.01); A61M 2205/7536 (2013.01); A61M 2205/8237 (2013.01); A61M 2209/045 (2013.01); **A61J 1/20** (2013.01)

> (2013.01); A61M 2205/3576 (2013.01); A61M

(57)ABSTRACT

A fill adapter system for an infusion pump assembly. The system includes a reusable fill adapter base, the base including a volume control mechanism to adjust an available fill volume of a reservoir of the infusion pump assembly and a pump mechanism configured to pump air into a fluid vial. The system also includes a vial adapter assembly including a first needle configured to penetrate a septum of the fluid vial for fluidly coupling the pump mechanism to the fluid vial and a second needle having a first end configured to penetrate the septum of the fluid vial and a second end configured to penetrate a septum of the reservoir of the infusion pump assembly to allow transfer of fluid from the fluid vial to the reservoir of the infusion pump assembly in response to air being pumped into the fluid vial and a needle carriage adapted to carry the first needle and the second needle, wherein the needle carriage slidably attached to the interior of the vial adapter assembly, wherein the needle carriage adapted to slide from a vial end of the vial adapter to a receptacle end of the vial adapter.

